



Prime Seal

Stain resistant acrylic sealer

5 Litres - N145

200 Litres - N148

DESCRIPTION:

A hard, clear, brilliant primer that keeps water, dirt and abrasive wear from penetrating into floors. Gives longer lasting protection. Ideal as a base for all floor finishes.

DIRECTIONS:

Floor preparation:

Strip floor thoroughly using FLASH STRIP liquefying stripper, making sure that all old film is removed, and allow to dry.

Application of sealer:

Using a clean mop or finish applicator, apply a thin even coat of prime seal and allow to dry for at least 30 minutes. A second coat of seal may be applied depending on the floor surface and appearance of the seal. After prime seal has completely dried, apply the recommended evolution 2000 floor finish as per instructions.

PHYSICAL AND CHEMICAL PROPERTIES:

Appearance:	milky emulsion
Odour:	Odourless
Specific Gravity:	1.00
PH:	7.5 +/- 0.5

FIRST AID MEASURES:

Ingestion:

Immediately rinse mouth with water. If swallowed do not induce vomiting. Give water to drink. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Eye Contact:

Immediately flush eyes with large amounts of water for at least 15 minutes while holding eyelids open. Transport to the nearest medical facility for additional treatment. Do not rub eyes or keep eyes closed.

Skin Contact:

Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.

Inhalation:

Remove the affected person out to a ventilated area. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.